

Specifications

		SCC-C641	SCC-C641P	SCC-643A	SCC-643AP	
Camera Type Image	Color	Color				
	Device	Super-HAD CCD				
	Size	1/4 inch				
	Pixels-Total	811 x 508	795 x 596	811 x 508	795 x 596	
Scanning	Pixels-Effective	768 x 494	752 x 582	768 x 494	752 x 582	
	System	Interlace				
	Horizontal Frequency-Internal Mode	15,734 Hz	15,625 Hz	15,734 Hz	15,625 Hz	
	Horizontal Frequency-Line-lock Mode	15,750 Hz	15,625 Hz	15,750 Hz	15,625 Hz	
	Vertical Frequency-Internal Mode	5994 Hz	50Hz	5994 Hz	50Hz	
Min. Scene Illumination	Vertical Frequency-Line-lock Mode	60 Hz	50 Hz	60 Hz	50 Hz	
	Color	0.3 Lux (Sense Up X4 30IRE)	0.01 Lux (Sense Up X128)	0.3 Lux (Sense Up X4 30IRE)	0.01 Lux (Sense Up X128)	
PAN/TILT	B/W	-	-	0.003 Lux	0.003 Lux	
	Speed-Manual Pan	08' /sec ~ 90' /sec				
	Speed-Preset Pan	240' /sec				
	Speed-Manual Tilt	08' /sec ~ 45' /sec				
	Speed-Preset Tilt	150' /sec				
	Range-Panning	360(endless)				
	Range-Tilting	0' /sec ~ 90' /sec				
	Number of Scan	1				
	Number of Auto PAN	1				
	Number of Preset	128				
	Number of Pattern	3				
	Functions	Number of Privacy Zone	-	-	-	8
		Day/Night	-	-	-	Yes
		Motion Detection	Yes			
		Wide Dynamic Range	-			
D-Zoom		Yes(2X ~ 10X)				
High Speed Shutter		Yes(OFF ~ 1/10K)				
Sense Up		Yes(X2 ~ X128)				
PIP		Off/On				
BLC		Off/On				
AGC		Off/On				
Line Lock		Off/On				
Camera ID		Max 12 Character				
Resolution		White Balance	ATW / AWC / MANUAL			
		Horizontal	480 TV Lines			
Video Output		Vertical	350 TV Lines			
	VBS 10Vp-p	VBS 10Vp-p				
S/N Ratio	52	52 dB				
	Lens	Focal Length				
Lens	Zoom ratio	36 ~ 792 mm				
	Aperture Ratio	22X				
	Viewing Angle -Tele	F16(Wide), F38(Tele)				
	Viewing Angle -Wide	2' 3"(H) x 1' 7"(V)				
	OSD	47' 9"(H) x 36' 9"(V)				
OSD	OSD	Yes				
	Alarm	Input				
Remote Control	Input	4				
	Output	3				
Environmental	RS485/RS-422	RS485 Half / Full Duplex, RS-422				
Conditions	Operating Temperature	-10 ° C ~ +50 ° C				
	Humidity	Less than 90%				
Power	Power Requirement	AC24V(60Hz) ±10%	AC24V(50Hz) ±10%	AC24V(60Hz) ±10%	AC24V(50Hz) ±10%	
	Power Consumption	18W				
	LED Indicator	Yes				
Physical Specification	Dimensions -Net	159.5(ø) x 177(H)				
	Weight-Net	1,700g				
	Loading Quantity(20/40ft)	756 / 1,776				
	Packing	378 x 308 x 275 mm				

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model