

Specifications

		SCC-B5203(S)	SCC-B5203(S)P
Camera Type	Color		Color
Image	Device		Super-HAD CCD
	Size		1/3 inch
	Pixels - Total	811 x 508	795 x 596
	Pixels - Effective	768 x 494	752 x 582
Scanning	System		Interlace
	Horizontal Frequency-Internal Mode	15,734 Hz	15,625 Hz
	Vertical Frequency-Internal Mode	5994 Hz	50 Hz
Min. scene Illumination	Color		0.3 Lux
PAN/TILT	Range-Panning		330° (Manual)
	Range-Tilting		15° ~ 90° (Manual)
Functions	BLC		On
	AGC		On
	ELC		On(Max.1/120Ksec)
	White Balance		ATW / AWC
Resolution	Horizontal		520 TV Lines
	Vertical		350 TV Lines
Video Output	VBS 1.0Vp-p		VBS 1.0Vp-p
S/N Ratio	S/N Ratio		50dB
Lens	Focal Length		3 mm
	Aperture Ratio		F2
	Viewing Angle		95° (H) x 71° (V)
Environmental Conditions	Operating Temperature		-10° C ~ +50° C
	Humidity		Less than 90%
Power	Power Requirement		DC12V+10%/ -5%
	Power Consumption		2W
Physical Specification	Dimensions(ø x H)-Net		85(ø) x 54(H) mm
	Weight-Net		125g
	Loading Quantity(20/40ft)		15,840 / 31,680
	Etc.-Body Color	B5203 : Black / B5203S : Silver	
	Packing		118 x 101 x 118 mm

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model